



GSX-R600W

1992

KEY FEATURES

Engine

- Compact 4-cylinder, 4-stroke DOHC engine
- High efficiency liquid-cooling system
 - Oil-jet piston cooling system
- Liquid-cooled oil cooling system Lightweight shim-under-bucket
- valve train
- 36mm Mikuni slingshot carburetors
 - Digital ignition system with maintenence-free battery
- Close ratio 6-speed transmission
 - Stainless steel 4 into 2 into 1

Frame/Suspension

- Rigid double-cradle aluminum frame
 Bolt-on seat support section
- Curved, G.P.-style aluminum
- swingarm Showa cartridge-type inverted
- front forks
 Link-type rear suspension with
- remote reservoir shock absorber 310mm front disk brakes with
- floating rotors & 4-piston calipers

 Adjustable front brake lever

 240mm rear disc brake with
- 2-piston caliper 3-spoke cast aluminum who
- 3-spoke cast aluminum wheels with radial tires
- New-style fairing with fresh air intake ducts
- Flush mounted halogen headlamps
 - 5.5 gallon fuel tank with additional frame sidecovers

Gourtesy of KAINASAKI-YAMA-ZUKI

PLEASE NOTE:

This product is in development and scheduled for March 1992 availability. These specifications are not final and are subject to change.

SPECIFICATIONS

Engine:

		cooled, DOHC, 16 valve, TSCC
Bore/Stroke:		65.0 x 45.2mm
Compression Ratio:		12.0:1
Carburetor:		Four Mikuni BST36SS
Lubrication:		Wet sump
Ignition:		Fully transistorized
Starter:		Electric
Transmission:		6 speed, constant mesh
Final Drive:		RK50GSVZ1 chain
Overall Length:		2085mm (82.1 in.)
Overall Width		725mm (28.5 in.)
Overall Height		1140 mm (44.8 in.)
Seat Height:		780 mm (30.7 in.)
Wheelbase:		1435mm (56.5 in.)
Ground Clearance:		130mm (5.1 in.)
Dry Weight:		208kg (459 lbs.) 212kg (467 lbs.) CA model
Suspension:	FRONT	Inverted telescopic, coil spring, spring
		preload fully adjustable, damping force
		compression 12-way and extension
		12-way adjustable
	REAR	Link type, coil spring, gas/oil damped,
		spring preload fully adjustable, damping
		force compression 12-way and rebound
		4-way adjustable.
Brakes:	FRONT	Dual hydralulic disc
	REAR	Single hydraulic disc
Tires:	FRONT	120/70-ZR-17
	REAR	170/160-ZR-17
Fuel Tank Capacity:		21.0 liter (5.5 gal.)
		18.5 liter (4.8 gal.) CA model
Colors:		White/Red, Black/Blue

